

USAF review completed. Approved For Release 2008/07/28 : CIA-RDP80T00246A000600780001-9

C-Q-N-F- I-D-E-N-7	'- I-A-L SEE BOTTOM OF	PAGE FOR SPECIAL CONTROLS, IF ANY
INFORMA	TION REPORT	This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C.
PREPARED AND DISSEMINATE	D BY	Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized per-
CENTRAL INT	ELLIGENCE AGENCY	son is prohibited by law.
COUNTRY Hungary	JSAF review completed.	<del>-</del>
Construction and	Transport Equipment	DATE DISTRIBUTED  12 Feb 1957  NO. OF PAGES  NO. OF ENCLS.  25
	ARMY review completed.	SUPPLEMENT TO REPORT # 25X1

THIS IS UNEVALUATED INFORMATION

This report is the result of a joint collection effort by the Air Force, the Army and CIA and is disseminated in accordance with the provisions of NSCID # 7

25X1

25X1

- 1. The ditcher /See sketch (a) 7 of Soviet origin is capable of digging ditches 60 cm wide and one meter deep. It is tractor-drawn and is mostly used in road construction.
- 2. The assault boat see sketch (b) is made of wood and powered by a 30 hp gasoline engine. The power unit, known as the "motor car," is a combination prime mover and rudder. It is made by the Budapest Small Motor Factory.
- 3. The Mocso utility boat /see sketch (1) /, which can accommodate 20 fully equipped personnel, can also be used for floating pontoons into position. It is powered by two 70-hp, 6-cylinder diesel engines (Csepel). The boat's twin screws not only propel but also serve as rudders.
- 4. The light and heavy pontoon (model unknown) /see sketch (d) I are of the same design. The difference is in the material used. The wooden, or light, pontoon has a carrying capacity of seven tons, and the steel, or heavy pontoon, used in pairs, can carry 70 tons. The pontoon consists of three sections: 10-meter bow, 12-meter center and 10-meter stern.
- 5. The first-class railroad lines (48.3 kg/m of rail) are now designed to earry Soviet railroad cars. The distance from the center of one track to the center of an adjacent track is four meters.
- 6. Construction has been started on a permanent overpass to carry two tracks over Villaryi St (formerly Szent Imre Herceg St) and Bajmoci St in Budapest. This work is to be finished in 1957. (AMS Series M973, sheet 3, Budapest 351.6 5260.9).
- A single-track railroad, with one bridge, has been built between Sukosd and Baja but it has not been used since Hungary's relations with Yugoslavia improved after Stalin's death.

			0-N-F-LD-	E., N.,	T I A.	<u>.I. </u>		 		 		
DISTRIBUTION	STATE	ARMY	NAVY.	1	IR ·		2 ,-					,
	100		astebu	UNIVERSITY OF	MERCY TOTAL	\$ 135 <b>4</b> .		 	•		(	6.

## C-O-N-F-I-D-E-N-T-I-A-L

8. Hungarian railroads are built according to norms designated as MNOSz (Magyar Nepkoztarsasag Orszagos Szabvanya -- Hungarian People's Republic Government Norm). The Hungarian standards are mostly based on the German EIN (Deutsche Industrie Normen).

9.	the bridge norm for first-class bridges:  **At distances of 1.30 m, seven times the load of 25 tons can be applied to two rails on a bridge. This represents the load of a theoretical locomotive."						
	classified CONFIDENTIAL, are these sketches	25X1					
	CISSILIED CONTIDENTIAL, SIE these skatches	25 <b>X</b> 1					

- (a) The ditcher described in paragraph 1.
- (b) The assault boat described in paragraph 2.
- (c) The Mocso utility boat described in paragraph 3.
- (d) The pontoons described in paragraph 4.


-end-

C-O-N-F-I-D-E-N-T-I-A-L



Approved For Release 2008/07/28 : CIA-RDP80T00246A000600780001-9

Sketch W



25X1


25X1

30 HP. - 2 CYLINDER - 4 CYCLE

25X1

CONTIDENTIAL

SKEtCH (C)




CSEPEL MOTOR - MANUFACTURED BY CSEPEL PLANT NEAR BUDAPEST

70 HP - 6 CYLINDER DIESEL ENGINE - 4 CYCLE

## Approved For Release 2008/07/28 : CIA-RDP80T00246A000600780001-9 CONFIDENTIAL

SKEtch (d)



## CONFIDENTIAL